Claims

5

25

30

- 1. A process for reducing the content of $NO_{\rm x}$ and $N_{\rm 2}O$ in gases, in particular in process gases and offgases, which comprises the measures:
- a) addition of at least one nitrogen-containing reducing agent to the NO_x and N_2O -containing gas in at least the amount required for complete reduction of the NO_x ,
- 10 b) addition of a hydrocarbon, of carbon monoxide, of hydrogen or of a mixture of one or more of these gases to the NO_x- and N_2O- containing gas for the reduction of the N_2O and
- c) introduction of the gas mixture into at least one reaction zone at temperatures of up to 450°C which contains one or more iron-laden zeolites.
- 2. The process as claimed in claim 1, characterized in that the nitrogen-containing reducing agent is 20 ammonia.
 - 3. The process as claimed in claim 1, characterized in that the reaction zone or zones contains an iron-laden zeolite which has channels made up of twelve-membered rings.
 - 4. The process as claimed in claim 3, characterized in that all channels of the iron-laden zeolite are made up of twelve-membered rings.
 - 5. The process as claimed in claim 4, characterized in that the iron-laden zeolite is of the BEA or FAU type.
- 35 6. The process as claimed in claim 1, characterized in that the nitrogen-containing reducing agent is ammonia and in that ethane, propane, butane, synthesis gas or LPG and in particular methane is used as

reducing agent for N_2O .

7. The process as claimed in claim 6, characterized in that an iron-laden zeolite of the BEA type is used as iron-laden zeolite.